

TECHNICAL CHARACTERISTICS

MATERIAL
 INSULATOR: NYLON 66
 FLAMABILITY RATING: UL94-V0
 COLOR: WHITE TRANSPARENT
 PITCH: 3.96MM

ENVIRONMENTAL
 OPERATING TEMPERATURE: -40 UP TO 105°C
 COMPLIANCE: LEAD FREE AND ROHS


ELECTRICAL
 CURRENT RATING: 7A
 WORKING VOLTAGE: 250V AC
 INSULATOR RESISTANCE: >1000 MOHM
 DIELECTRIC WITHSTANDING VOLTAGE: 1500V AC/MN

PACKAGING
 BAG

DIMENSION
 A = 3.96 x (NB. PIN - 1)
 B = 3.96 x (NB PIN) + 0.51

RoHS Compliant

G			
F			
E	12-MAY-09	NEW DRAW	JP
D	26-MAR-07	DRAW	EC
C	26-JAN-07	DRAW	EC
B	31-MAR-04	LEAD FREE	JP
A	14-MAY-02	PDF	JP
REV	DATE	FILE	BY



GENERAL TOLERANCE
 .X = +/- 0.2
 .XX = +/- 0.15



APPROVAL: RJ

UNIT: MM
 SCALE:
 SHEET: 1/1
 DRAW: PEARL

DESCRIPTION: 3.96MM FEMALE TERMINAL HOUSING
 WERI PART NO: 6450 xx 113322

SIZE
A4